Addressable Pull Stations and Manual Call Points

Discovery, XP95, XP95A

XP95A Dual Action Addressable Manual **Pull Station**



The Dual Action Addressable Manual Pull Station features translucent plastic at the centre, allowing visibility of an internal LED that indicates alarm condition and polling status. The unit is addressable using a DIP switch protected within the pull station. The pull station may be flush mounted on a single gang work box or use an optional back cover (56000-006).

☐ Control panel compatibility

□ Key lock

☐ Easily resettable

☐ Lightweight polycarbonate housing

☐ Approvals: FM, UL

55000-041: XP95A Open Area Sounder (Red)

55000-042: XP95A Open Area Sounder (White)

Intelligent Manual Call Point



The Intelligent Manual Call Point has been designed to operate on a loop of intelligent fire detection devices. The Intelligent Manual Call Point will operate with compatible Apollo control equipment using the digital XP95, Discovery and CoreProtocols.

☐ Resettable operating element

□ E-Z fit connector system for installation

☐ EN 54-11 & EN 54-17 Certified (Red version only)

☐ Continuity link for cable insulation testing

☐ Suitable for semi flush or surface mounting

☐ Approvals*: SBSC, VdS, FG, LPCB, BOSEC, CPR, CPR (CN) **XP95 Manual Call Point**



The XP95® Manual Call Point has been designed to operate on a loop of intelligent fire detection devices and when activated interrupts the polling cycle for a very fast response. The XP95 Manual Call Point is intended for indoor applications and is available in two versions, with and without isolator.

☐ Easily resettable element

☐ Unique 'Plug and Play' installation

 $\hfill\Box$ Continuity link for wiring test before commissioning

☐ Reports an alarm in under 0.2 seconds

□ EN54-11 & EN54-15

☐ Approvals*: SBSC, CCCf, LPCB, CPR

Discovery Waterproof Manual Call Point



The Waterproof Addressable Manual Call Point has been designed to operate on a loop of intelligent fire detection devices and when activated interrupts the polling cycle for a very fast response. Available with and without isolator. It is intended for outdoor applications or areas where water ingress or high humidity is a problem.

☐ Resettable operating element

☐ Ergonomic reset key

☐ Captive screws for easy installation

☐ Flashing Poling LED Option

□ EN 54-11 & EN 54-17

□ IP56 rated (with IP67 rated electronics enclosure)

☐ Approvals*: SBSC, FG, CPR, CPR (CN)

SA5900-908: Intelligent Manual 55100-905: XP95 Manual Call Call Point (Red)

SA5900-903: Intelligent Manual Call Point (White)

SA5900-904: Intelligent Manual Call Point (Yellow)

58200-950: Discovery Waterproof Manual Call Point (Red)

58200-951: Discovery Waterproof Manual Call Point with isolator (Red)

58200-953: Discovery Waterproof Manual Call Point with isolator (Yellow)

*Approvals

SBSC Svensk Brand & Sakerhets Certifiering AB Certificate (Scandinavia)

Page 7

FG Forsikringsselskapenes Godkjennelsesnevnd (Norway) BOSEC - Belgian Organisation for Security Certification

CCCf - China Certification Center for Fire Products Certificate of Constancy of Performance (EU) - Certificate of Constancy of Performance Beijing









All data is supplied subject to change without notice

Approvals registered under Apollo Fire Detectors Ltd

